

Models:

RT-MAg-004	– Grid Sieve Set (2.5 – 50 mm gap width, 14 pcs)
RT-MAg-004/2,5	– Grid Sieve, 2.5 mm gap width
RT-MAg-004/3,15	– Grid Sieve, 3.15 mm gap width
RT-MAg-004/4	– Grid Sieve, 4.0 mm gap width
RT-MAg-004/5	– Grid Sieve, 5.0 mm gap width
RT-MAg-004/6,3	– Grid Sieve, 6.3 mm gap width
RT-MAg-004/8	– Grid Sieve, 8.0 mm gap width
RT-MAg-004/10	– Grid Sieve, 10.0 mm gap width
RT-MAg-004/12,5	– Grid Sieve, 12.5 mm gap width
RT-MAg-004/16	– Grid Sieve, 16.0 mm gap width
RT-MAg-004/20	– Grid Sieve, 20.0 mm gap width
RT-MAg-004/25	– Grid Sieve, 25.0 mm gap width
RT-MAg-004/31,5	– Grid Sieve, 31.5 mm gap width
RT-MAg-004/40	– Grid Sieve, 40.0 mm gap width
RT-MAg-004/50	– Grid Sieve, 50.0 mm gap width

Accessories:

RT-MAg-004/zB	– Cabinet for grid sieves
---------------	---------------------------

Standards:

EN 933-3

NF P18-561, UNI 8520-18, NLT 354

Description:

Grid sieves used for determination the flakiness index of the aggregate. Made entirely from stainless steel.

Weight (approx.) – 2 kg

Dimensions – 260x260x75 mm

