General Lab Equipment

VACUUM DESICCATORS



Models:

RT-MG-003/4.5L – Vacuum Desiccator (lightweight type), 4.5 L capacity – Vacuum Desiccator (lightweight type), 12 L capacity – Vacuum Desiccator (heavy type), 20 L capacity

RD-MG-003/30S - Vacuum Desiccator (heavy type), 30 L capacity

Accessories:

RD-MG-003/zSP – Two-stage Vacuum Pump, 42 L/min RD-MG-003/zPP – Two-stage Vacuum Pump, 100 L/min

RD-MG-003/zDP – Diaphragm Vacuum Pump

RT-MG-003/zG1 — Vacuum Gauge complete with connections and

bleed/regulation pin valve

RT-MG-003/zG3 – Vacuum Gauge complete with connections for

3 desiccators and bleed/regulation pin valve

RD-MG-003/zDU — Air Drying Unit for use with silica gel

RD-MG-003/zSG - Silica gel, 1 kg

RT-MG-003/zD - Desiccator Dolly for RT-MG-003/20S and

RT-MG-003/30S



EN 12697-5, EN 12697-12



RT-MG-003/12L



RT-MG-003/20S

Description:

RT-MG-003 vacuum desiccators are used for determining the theoretical maximum density of uncompacted asphalt mixtures, as well as for determining the water sensitivity of bituminous specimens according to EN 12697-12. RT-MG-003/4.5L & RT-MG-003/12L are lightweight type desiccators with 4.5 L and 12 L capacity made from robust transparent plastic.

RT-MG-003/20S & RT-MG-003/30S are heavy type desiccators with 20 L and 30 L capacity made from stainless steel with transparent lid.

All the above vacuum desiccators have to be connected with suitable vacuum pump and vacuum gauge with bleed/regulation pin valve (see accessories).

The vacuum desiccator supplied complete with cover clamps (3 pcs.), quick-release connection, vacuum hose (2.0 m) and internal stainless-steel shelf (with one level for RT-MG-003/4.5L & RT-MG-003/12L, two levels for RT-MG-003/20S, and three levels for RT-MG-003/30S).



RD-MG-003/zDP



RD-MG-003/zPP



RT-MG-003/zG1



RT-MG-003/zG3



RT-MG-003/zS

Technical specifications:

	RT-MG-003/4.5L	RT-MG-003/12L	RT-MG-003/20S	RT-MG-003/30S
Capacity	4.5 L	12 L	20 L	30 L
Internal diameter	190 mm	290 mm	280 mm	
Internal height	175 mm	195 mm	330 mm	495 mm
Desiccator material	transparent plastic		Stainless steel	
Lid material	transparent plastic			
Weight (approx.)	3.8 kg	7.3 kg	12.4 kg	16.0 kg

